



Manual Rope Grab

Specification Sheet

Manual Rope Grab

Item# 10096511

The Safety Works rope grab is designed as a means of fall arrest between a worker wearing a compatible full-body harness and a suitable fall arrest anchorage. They can also be used in restraint systems to prevent workers from reaching the leading edge of a fall hazard. Applications include roofing, ladder climbing, general construction and tower climbing.

Features

- > Easy to operate
- > Manually squeeze the device to move along rope
- > For use over a twisted rope life line with a diameter of 5/8"
- > Connected with a shock pack that has a snap hook at the end for attachment to the harness
- > May be used to support a Maximum 1
- > Personal Fall Arrest System (PFAS)
- > Maximum free fall is 6'

Technical Data

Material	Steel
Color	■ Black
Sizing	One Size
Certifications	Meets OSHA 1926.104 & ANSI Z359.1 2017 requirements
Weight Capacity Range	130-310 lbs (including all clothing, tools, and equipment)
Additional Requirements	Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs
Packaging	6 per case
Case Dimensions	12.7" x 7.4" x 8.9"
Case Weight	11 lbs / 5 kg
COO	India

Barcode

Item	Barcode
10096511	641817019450



SAFETY WORKS®

968 Albany Shaker Road > Latham, New York 12110 > 1.800.969.7562 > www.safetyworks.com

This document and the information contained herein is the property of Safety Works and may not be used or reproduced without permission. Product users should conduct all appropriate testing or other evaluations to determine the suitability of Safety Works products for a particular purpose or use within a particular environment. SAFETY WORKS DISCLAIMS ALL WARRANTIES OTHER THAN AS EXPRESSLY PROVIDED.